

H insulation kit

Project Information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Plastic
Subcomponent Material	H-Insulation kit 2X (140-175-200), half shell: ABS (thermoplastic material made of acrylonitrile, butadiene and styrene) Seal adhesive cartridge: Bostik 2639 Body-bound rivets: Plastic Metal sheets



Product Information and application use

The H-insulation Kit makes an insulated H-connection between single and twin-style pre-insulated pipe products with a jacket size of 5.5", 6.9" and 7.9". The kit features two shells, stainless steel bolts, plastic pins and joint-sealing compound. Use with Uponor Rubber End Caps only.

Part name	Part no.	Weight per UOM [lbs/UOM]
H-Insulation Kit, 5.5", 6.9", 7.9	1007355	42

Installation	Related applications
If needed, install reducing sockets before couplings. Conduct hydraulic pressure test after installing couplings. Use End Caps (required) at all ends of the piping system to ensure insulation integrity. Refer to the Insulation Kit Mounting Instructions.	Pre-Insulated Pipe Systems PEX-a Plumbing Systems (Canada only)

Footnotes	Contact information
-	<div>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</div> <div>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</div>