

ASTM WIPEX fittings

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Brass
Subcomponent Material	Body: DZR (dezincification-resistant) brass
	Clamp ring: DZR brass
	Bolt: Stainless steel
	Nut: Stainless steel
	Washer: Stainless steel
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes



Product information and application use

WIPEX™ Fittings are used for all types of Uponor's crosslinked polyethylene (PEX-a) tubing applications. Dezincification-resistant (DZR) brass fittings are safe for direct burial in soil.

Part name	Part no.	End Type 1	End Type 2	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]
WIPEX Fitting 1" PEX x 1" NPT	5550010	Compression 1"	MNPT 1"	-	-	-	0.63
WIPEX Fitting 4" x 4" NPT	5550040	Compression 4"	MNPT 4"	5.52	5.551	4.724	10

Part name	Part no.	Codes	Standards	Listings
ASTM WIPEX fittings	All	IMC UMC	CSA B137.5 NSF-14 ASTM F877	IAPMO-ES

Installation

Use DZR brass adapters to transition Uponor PEX tubing to male NPT thread. Use EPDM O-rings between the different parts for sealing. For more information, refer to the Uponor WIPEX Fittings Instruction Sheet.

Related applications

- Pre-Insulated Pipe Systems
- Radiant Heating and Cooling Systems
- Permafrost Prevention Systems
- Turf Conditioning Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517