

Ecoflex potable PEX plus accessories

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Subcomponent Material

Ambient temperature min. [F] -40 °
 Ambient temperature max. [F] 482 °

Product information and application use

Uponor heat-trace end seal is part of a universal power termination and splicing system for Uponor Ecoflex® potable PEX plus pre-insulated piping systems.



Part name	Part no.	Weight per UOM [lbs/UOM]
Heat-trace Power Terminal Block	5992000	0.3
Heat-trace End Seal	5993000	0.05
Heat-trace Tee Splice	5994000	0.3

Part name	Part no.	Codes	Standards	Listings
Ecoflex potable PEX plus accessories	All	-	-	IECEx SIR 11.0136U

Installation

Simply cut back one wire $\frac{1}{4}$ " (6mm) and push it into the end seal. For additional information, refer to the Uponor Ecoflex Pre-insulated Pipe Systems Design and Installation Manual.

Related applications

Pre-Insulated Pipe Systems
 Permafrost Prevention Systems
 PEX-a Plumbing Systems

Notes

Voltage Range 220 to 277

Voltage Range 220 to 277.

Footnotes

Contact information

Uponor Inc.
 5925 148th Street West
 Apple Valley, MN 55124
 T 800.321.4739
 F 952.891.2008

Uponor Ltd.
 6510 Kennedy Road
 Mississauga, ON L5T 2X4
 T 888.594.7726
 F 800.638.9517