

Manifold wall cabinets

Project information


Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material Metal

Product information and application use

The Uponor Manifold Wall Cabinet is adjustable to accommodate a manifold mounted in either a 2 x 4 or 2 x 6 stud wall. This is a recessed-style cabinet and comes with a removable door-trim package. You can mount an Uponor Zone Control Module inside the cabinet for ease of wiring and away from exposure or possible damage.



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	Weight per UOM [lbs/UOM]
Manifold Wall Cabinet, 35.5" H x 24" W x 3.5" D	A2603524	35.693	25.25	3.91	35.05	24	28
Manifold Wall Cabinet, 35.5" H x 30.5" W x 3.5" D	A2603530	35.75	31.75	3.6	35.05	30.5	35
Manifold Wall Cabinet, 35.5" H x 39" W x 3.5" D	A2603539	40.25	35.75	3.9098	35.05	39	48

Installation

Set the manifold cabinet into the wall cavity, flush with the opening. In a 2 x 4 wall, the manifold cabinet must be inserted to the back of the stud. In a 2 x 6 wall, the manifold cabinet should be approximately 1 to 2 inches from the back of the stud. Attach the manifold box to the stud framing with wood screws. Align the four door-trim brackets with the threaded posts and wing nuts located at the top and bottom on the left and right sides of the manifold box. Slide the door-trim inward until frame is tight to the wall. Secure the frame by tightening the wing nuts. Mount the latch to the door using supplied hardware and attach the door to the door trim. For more information, refer to the Manifold Wall Cabinet instruction sheet.

Related applications

- Radiant Heating and Cooling Systems
- Turf Conditioning Systems
- Permafrost Prevention Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517