
Stainless-steel manifold assembly, 1" with flow meter

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Stainless Steel
Subcomponent Material	Manifold Components: Brass CW614N-UNI EN12164, CW617N-UNI EN12165
Manifold size	1 inch
Loop Cv	1.1 Cv
End type 1	ISO 228-G 1-1/4"
End type 2	ISO 228-G 3/4"
Temp/pressure ratings	68 °F (20 °C) at 145 psi (10 bar) 158 °F (70 °C) at 87 psi (6 bar) 194 °F (90 °C) at 44 psi (3 bar)
Max. fluid flow rate	14 gpm
Prop 65 label required?	Yes



Product information and application use

The 1" Stainless-steel Manifold Assembly with flow meter comes fully assembled and ready for installation. Use the included flow meters located on the supply manifold to balance the loops across the manifold. The return manifold comes equipped with isolation valves for easy loop isolation. For multiple zoning on the manifold, the black caps are removed and replaced with Uponor Thermal Actuators. The manifold body ends have R32 union connections and the loop outlets have R20 male threads. The included manifold supply and return ball valves come with an R32 x 1" NPT connection.

	Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	G [inch]	H [inch]	Weight per UOM [lbs/UOM]
	Stainless-steel Manifold Assembly, 1" with flow meter, B&I, ball valve, 4 loops	A2700402	15.097	14.119	3.842	1.969	5.488	1.55	2.05	10.2	11.16
	Stainless-steel Manifold Assembly, 1" with flow meter, B&I, ball valve, 5 loops	A2700502	17.065	14.119	3.842	1.969	5.488	1.55	2.05	12.198	12.2
✔	Stainless-steel Manifold Assembly, 1" with flow meter, B&I, ball valve, 7 loops	A2700702	21.002	14.119	3.842	1.969	5.488	1.55	2.05	16.149	12.22
	Stainless-steel Manifold Assembly, 1" with flow meter, B&I, ball valve, 10 loops	A2701002	26.908	14.119	3.842	1.969	5.488	1.55	2.05	22.032	14.92
	Stainless-steel Manifold Assembly, 1" with flow meter, B&I, ball valve, 12 loops	A2701202	30.845	14.119	3.842	1.969	5.488	1.55	2.05	25.994	16.72

Installation

The 1" Stainless-steel Manifolds are fully assembled and ready for installation. Manifold assembly comes with mounting brackets, isolation valves, balancing valves, fill/purge ports, air vents, ball valves, temperature gauges and end caps. Manifold adapters and fittings are sold separately. For further information, refer to the Uponor Stainless-steel Manifold Installation Guide.

Related applications

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

Hydronic Heating and Cooling Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2026 Uponor North America. All Rights Reserved