

# End caps with vent

## Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

## Technical data

Material	Brass
Manifold size	1 inch
End type 1	ISO 228-G 1-1/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Max. fluid flow rate	21 gpm
Prop 65 label required?	Yes

## Product information and application use

The End Cap with Vent, R32, caps the end of the TruFLOW™ Jr. modular manifolds. It comes complete with a swivel drain valve and a manual air vent. Includes required Manifold Gasket (A2403232).



Part name	Part no.	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]
End Cap with Vent, R32	A2803250	3.937	3.053	1.969	0.9

Installation	Related applications
Use with TruFLOW Jr. modular manifolds (not preassembled). Use the End Cap with Vent on the top manifold, following procedures outlined in the Uponor TruFLOW Jr. instruction sheet.	Radiant Heating and Cooling Systems

## Notes

Connection:  
1½" BSPP

Footnotes	Contact information
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008  Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517