

# Three-way mixing valves

Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data	
Subcomponent Material	Brass
	Brass (chrome-plated)
	Modified Teflon®
	Ethylene propylenediene monomer(EPDM) rubber
Ambient humidity non-condensing max [%]	90
Prop 65 label required?	Yes

Product information and application use
N/A



Part name	Part no.	A [inch]	B [inch]	C [inch]	Operating voltage AC [VAC]	Weight per UOM [lbs/UOM]
3/4" Three-way Mixing Valve, (CV=4.5)	A3040075	4.702	4.383	2.42	24	1.5
1" Three-way Mixing Valve, (CV=4.5)	A3040100	4.702	4.383	2.42	24	-

Part name	Part no.	Codes	Standards	Listings
Three-way mixing valves	All	-	Class II wiring	-

Installation	Related applications
N/A	-

Notes
3/4" Cv=4.5 Service: Closed-system hot and cold water Maximum 50% glycol
1" Cv=4.5 Service: Closed-system hot and cold water Maximum 50% glycol Maximum operating pressure: 300 psi (2,100 kPa) Maximum shutoff pressure: 125 psi (875 kPa)

Footnotes	Contact information	
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517