

QS-style coupling nipples

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Brass
End type 1	ISO 228-G 3/4"
End type 2	ISO 228-G 3/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

Product information and application use

The Uponor QS-style Coupling Nipple is available in R20 and R25 thread. It is used with compression fittings to connect 5 /16", 3/8", 1/2", 5/8" or 3/4" Wirsbo hePEX™ pipe in radiant heating and cooling applications. Note that R25 is for 5/8" and 3/4" pipe only.



Part name	Part no.	Codes	Standards	Listings
QS-style coupling nipples	A4322020	-	ASTM F877 R20: ISO 228-G 3/4"	-

Installation	Related applications
Corresponding QS-style fitting assembly threads onto QS-style Coupling Nipple fitting for repairs. For more information, refer to the Uponor Radiant Installation Handbook.	Radiant Heating and Cooling Systems

Footnotes	Contact information
-	<div>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</div> <div>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</div>