

ProPEX lead-free (LF) brass fire sprinkler accessories

| Project information | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

Prop 65 label required? Yes



| Part name | Part no. | A [inch] | B [inch] | C [inch] | Material group | Subcomponent Material | Equivalent length branch [ft] | End Type 1 | Operating Temperature 1 [°F] | Operating Temperature 2 [°F] | Operating Temperature 3 [°F] |
|---|-------------|-------------|-------------|-------------|-------------------|---|-------------------------------------|------------------|------------------------------------|------------------------------------|------------------------------------|
| Fire Sprinkler Adapter Mounting Bracket, 3/4" and 1 | A7750700 | 3.171 | 2.484 | 1.839 | Metal | 1050 Annealed (spheroidized) spring steel | - | - | - | - | - |
| Fire Sprinkler Adapter Push-on Nut, 25/pkg. | F7000005 | 2.125 | 0.233 | 2.125 | Steel | - | 0 | ProPEX | 73 | 180 | 200 |

| Part name | Part no. | Weight per UOM [lbs/UOM] |
|---|----------|--------------------------|
| Fire Sprinkler Adapter Mounting Bracket, 3/4" and 1 | A7750700 | 0.17 |
| Fire Sprinkler Adapter Push-on Nut, 25/pkg. | F7000005 | 0.01 |

| Part name | Part no. | Codes | Standards | Listings |
|----------------------------------|----------|-------|-----------|----------|
| ProPEX lead-free (LF) brass fire | All | - | UL 1821 | - |

| Installation | Related applications |
|--------------|-------------------------------|
| - | AquaSAFE™ Fire Safety Systems |

| Footnotes | Contact information | | |
|-----------|------------------------|-------------------------|--|
| | Uponor Inc. | Uponor Ltd. | |
| | 5925 148th Street West | 6510 Kennedy Road | |
| • | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 | |
| | T 800.321.4739 | T 888.594.7726 | |
| | F 952.891.2008 | F 800.638.9517 | |