

HDPE corrugated sleeves

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material PEHD

Product information and application use

High-density Polyethylene (HDPE) Corrugated Sleeves are used in hot and cold potable-water distribution systems, primarily in commercial applications where the potable tubing is installed in the slab. Designed for use with Uponor AquaPEX® crosslinked polyethylene (PEX-a) tubing, the sleeve provides protection during installation and allows for removal and replacement of the tubing, if necessary. This product can also be used in radiant heating and cooling systems with Wirsbo hePEX™ tubing. However, if using Uponor AquaPEX tubing (which does not have an oxygen barrier), the tubing can only be used in systems containing no ferrous corrodible components or where ferrous components are isolated from the tubing.



Part name	Part no.	Codes	Standards	Listings
HDPE corrugated sleeves	All	-	-	UL 263 CAN/ULC-S101

Installation	Related applications
Tie sleeving to rebar with standard steel wire or other fastening devices. Corrugated sleeves will fit in all Uponor concrete floor tube brackets. Refer to the Uponor Professional Plumbing Installation Guide or Radiant Heating Installation Handbook for additional information.	PEX-a Plumbing Systems Radiant Heating and Cooling Systems

Notes
Application Temperature Continuous Operation of Sleeve:  5°F (-15°C) to 158°F (70°C)

Footnotes	Contact information
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008  Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517