

Uponor AquaPEX blue coils

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	PEX
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)

Product information and application use

Uponor AquaPEX® blue tubing is an Engel-method, PEX-a pipe designed for cold potable water distribution systems, but can also be used in radiant heating and cooling systems containing no ferrous corrodible components or where ferrous components are isolated from the tubing

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Part name	Part no.	Inner diameter coil [mm]	Outer diameter coil [mm]	Inner diameter pipe [mm]	Outer diameter pipe [mm]	Weight per UOM [kg/UOM]
1/2" Uponor AquaPEX Blue, 100-ft. coil	F3040500	400.05	596.9	12.07	15.88	2.722
1/2" Uponor AquaPEX Blue, 300-ft. coil	F3060500	500.38	812.8	12.07	15.88	8.165
1/2" Uponor AquaPEX Blue, 1,000-ft. coil	F3120500	400.05	812.8	12.07	15.88	24.494
3/4" Uponor AquaPEX Blue, 100-ft. coil	F3040750	400.05	812.8	17.04	22.22	4.536
3/4" Uponor AquaPEX Blue, 300-ft. coil	F3060750	558.8	812.8	17.04	22.22	15.422
1" Uponor AquaPEX Blue, 100-ft. coil	F3041000	576.58	812.8	21.9	28.58	9.072
1" Uponor AquaPEX Blue, 300-ft. coil	F3061000	576.58	812.8	21.9	28.58	25.401

Part name	Part no.	Codes	Standards	Listings
Uponor AquaPEX blue coils	All	UPC IMC NBC of Canada IPC IBC IRC UMC NSPC UFGS NPC of Canada	ASTM E119 UL 263 ASTM F1960 ASTM E84 ASTM F2023 ASTM E814 ULC S115 CSA B214 CSA B137.5 NSF/ANSI 14 NSF/ANSI/CAN 61 ASTM F876 ASTM F877 ULC S102.2 ULC S101	cNSFus-pw IAPMO-ES ICC-ES- PMG CSA CCMC PPI TR-4 cQAlus P321 UL U.P.Code BMEC

Installation	Related applications
Approved fitting system is ProPEX®. Refer to the Uponor PEX Piping Systems Design and Installation Manual or the Uponor PEX Piping Systems Installation Guide for more information.	PEX-a Plumbing Systems

Footnotes	Contact information
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517