

PEX stand-up brackets

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Plastic
Subcomponent Material	PVC
Prop 65 label required?	Yes

Product information and application use

Use the PEX Stand-up Bracket in residential slab or commercial multi-floor construction. The brackets are available in either single-tube or five-tube configurations. The bracket supports up to 1" Uponor hePEX™ plus or Uponor AQUAPEX® tubing, or a 1" utility-grade, polyethylene sleeving.



Part name	Part no.	Weight per UOM [lbs/UOM]
Single-tube PEX Stand-up Bracket for 1/2" PEX	F5801000	0.5
Five-tube PEX Stand-up Bracket for 1/2" PEX	F5805000	1.1

Installation	Related applications
Screw or nail the 3/4" fastening tab to the floor or concrete forms. Secure the brackets to the deck form. Then install the 1/2" PEX tubing in the brackets, either with the 1/2" PEX tubing alone or with the 1/2" PEX tubing sleeved inside corrugated polyethylene carrier tube. Wire the tube at the top of bracket to bracket at the wiring tab.	PEX-a Plumbing Systems Radiant Floor Heating and Cooling Systems

Footnotes	Contact information
-	<div>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</div> <div>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</div>