

Pre-insulated Uponor Aquapex coils

Project Information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-----------------------|--|
| Material | PEX |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |

Product Information and application use

Pre-insulated Uponor AquaPEX® tubing is durable, flexible, corrosion-resistant and encased in 1/2" PEX-foam insulation to insulate potable water lines and meet national, state and local energy codes. The tubing is approved for use in hot and cold domestic potable water systems, residential fire safety and hydronic radiant heating and cooling systems containing no ferrous corrodible components or where ferrous components are isolated from the tubing. This product is approved for direct burial in soil and concrete

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



| Part name | Part no. | Inner diameter coil [inch] | Outer diameter coil [inch] | Coil width [inch] | Inner diameter pipe [inch] | Outer diameter pipe [inch] | R value | Weight per UOM [lbs/UOM] |
|--|----------|----------------------------|----------------------------|-------------------|----------------------------|----------------------------|---------|--------------------------|
| 1/2" Pre-insulated Uponor AquaPEX with 1/2" insulation, 100-ft. coil | F6040500 | 19 | 30 | 8.5 | 0.475 | 0.625 | 3.9 | 8 |
| 1/2" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6150500 | 19 | 36 | 12.5 | 0.475 | 0.625 | 7.5 | 11 |
| 3/4" Pre-insulated Uponor AquaPEX with 1/2" insulation, 100-ft. coil | F6040750 | 19 | 32 | 12.5 | 0.671 | 0.875 | 3.6 | 12.8 |
| 1" Pre-insulated Uponor AquaPEX with 1/2" insulation, 100-ft. coil | F6041000 | 19 | 31 | 12.5 | 0.862 | 1.125 | 3.4 | 21 |
| 1" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6151000 | 19 | 40 | 14 | 0.862 | 1.125 | 6.4 | 30.2 |
| 1 1/4" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6151250 | 27 | 40.5 | 12 | 1.054 | 1.375 | 6.1 | 39.2 |
| 3/4" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6150750 | 19 | 39 | 12.5 | 0.671 | 0.875 | 7.9 | 22 |

| Part name | Part no. | Codes | Standards | Listings |
|------------------------------------|----------|---|---|---|
| Pre-insulated Uponor Aquapex coils | All | IMC UPC IBC IRC NBC of Canada IPC UFGS NPC of Canada UMC NSPC | ASTM F1960 ASTM F876 ASTM F2023 ASTM E814 ULC S115 ASTM F877 CSA B137.5 CSA B214 NSF-61 ULC S101 NSF-14 | IAPMO-ES ICC-ES-PMG CCMC PPI TR-4 CSA UL U.P.Code cQAlus P321 |

In addition, the following parts have additional codes, standards, or listings:

| | | | | |
|--|----------|--|---------|--------------|
| 1/2" Pre-insulated Uponor AquaPEX with 1/2" insulation, 100-ft. coil | F6040500 | | | cNSFus-pw |
| 1/2" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6150500 | | | cNSFus-pw |
| 3/4" Pre-insulated Uponor AquaPEX with 1/2" insulation, 100-ft. coil | F6040750 | | UL 1821 | cNSFus-pw-fs |
| 1" Pre-insulated Uponor AquaPEX with 1/2" insulation, 100-ft. coil | F6041000 | | UL 1821 | cNSFus-pw-fs |
| 1" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6151000 | | UL 1821 | cNSFus-pw-fs |
| 1 1/4" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6151250 | | UL 1821 | cNSFus-pw-fs |
| 3/4" Pre-insulated Uponor AquaPEX with 1" insulation, 100-ft. coil | F6150750 | | UL 1821 | cNSFus-pw-fs |

| Installation | Related applications |
|---|---|
| <p>Approved fitting system is ProPEX®. 1 Refer to the ProPEX Connections Instructional Guide, Uponor Piping Pocket Guide, Plumbing Design Assistance Manual (PDAM), Complete Design Assistance Manual (CDAM), Hydronic Piping Design Assistance Manual (HPDAM) or AquaSAFE™ Residential Fire Sprinkler Installation Guide for more information.</p> | <p>PEX-a Plumbing Systems Radiant Heating and Cooling Systems Hydronic Piping Systems</p> |

Notes

Operating condition limits (hydrostatic ratings):
 ½"-2" Uponor AquaPEX® White only: 120°F (49°C) at 130 psi (896 kPa)

Operating condition limits (hydrostatic ratings):
 ½"-2" Uponor AquaPEX® White only: 120°F (49°C) at 130 psi (896 kPa)

| Footnotes | Contact information | |
|-----------|--|--|
| - | <p>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</p> | <p>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</p> |