

PEX-a pipe supports

| Project information | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Product information and application use

PEX-a Pipe Support is a non-combustible, self-gripping, galvanized-steel channel for crosslinked polyethylene (PEX-a) pipe. It provides continuous, uninterrupted support of PEX-a pipe, allowing hanger placement similar to that of metallic pipe. Use PEX-a Pipe Support in conjunction with uninsulated Uponor AquaPEX® or Wirsbo hePEXTM PEX-a pipe in ASTM E84 plenum applications. The PEX-a pipe with pipe support can be insulated with typical CTS (copper tube size) pipe insulation. PEX-a Pipe Support is offered in 9-foot lengths and comes with nylon-coated, stainless-steel strapping.



| Part name | Part no. | A [inch] | B [inch] | C [inch] | Material group | Subcomponent Material | Prop 65 label required? | Weight per UOM [lbs/UOM] |
|---|----------|----------|----------|----------|-------------------|---|-------------------------------|--------------------------------|
| 1/2" PEX-a Pipe Support, 9-ft. length | F7040500 | 108 | 0.677 | 0.406 | Metal | Commercial- grade (Type B) galvanized steel | - | 1.1 |
| 3/4" PEX-a Pipe Support, 9-ft. length | F7040750 | 108 | 0.921 | 0.552 | Metal | Commercial- grade (Type B) galvanized steel | No | 1.5 |
| 1" PEX-a Pipe Support, 9-ft. length | F7041000 | 108 | 1.163 | 0.698 | Metal | Commercial- grade (Type B) galvanized steel | - | 1.91 |
| 1 1/4" PEX-a Pipe Support, 9-ft. length | F7041250 | 108 | 1.396 | 0.837 | Metal | Commercial- grade (Type B) galvanized steel | - | 2.1 |
| 1 1/2" PEX-a Pipe Support, 9-ft. length | F7041500 | 108 | 1.623 | 0.973 | Metal | Commercial- grade (Type B) galvanized steel | - | 2.5 |
| 2" PEX-a Pipe Support, 9-ft. length | F7042000 | 108 | 2.095 | 1.256 | Metal | Commercial- grade (Type B) galvanized steel | - | 3.6 |
| 2 1/2" PEX-a Pipe Support, 9-ft. length | F7042500 | 108 | 2.562 | 1.537 | Metal | Commercial- grade (Type B) galvanized steel | - | 4.6 |
| PEX-a Pipe Support Strapping for 1/2", 3/4" and 1" PEX | Q7410510 | - | - | - | Plastic | - | - | 0 |
| 3" PEX-a Pipe Support, 9-ft. length | F7043000 | 108 | 3.024 | 1.81 | Metal | Commercial- grade (Type B) galvanized steel | - | 6.2 |
| PEX-a Pipe Support Strapping for 1 1/4", 1 1/2" and 2" PEX | Q7411220 | - | - | - | Plastic | - | - | 0.01 |
| PEX-a Pipe Support Strapping for 2 1/2", 3", 3 1/2" PEX | Q7412540 | - | - | - | Plastic | - | - | 0.01 |

| Part name | Part no. | Codes | Standards | Listings |
|---------------------|----------|---------|-----------|---------------------|
| PEX-a pipe supports | All | IMC UMC | ASTM E84 | QAI P321 (up to 3") |

Installation Related applications

Install PEX-a Pipe Support vertically or horizontally for plenum and non-plenum applications. Refer to the Uponor PEX-a Pipe Support Instruction Sheet for installation guidelines.

PEX-a Plumbing Systems
Radiant Heating and Cooling Systems
AquaSAFE™ Fire Safety Systems

Footnotes Contact information

Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517