

PEX clips

Project Information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Plastic
Subcomponent Material	Nylon

Product Information and application use

Uponor PEX Clips are designed to suspend crosslinked polyethylene (PEX) tubing below the underside of a subfloor in a joist cavity installation.



Part name	Part no.	A [mm]	B [mm]	C [mm]	Prop 65 label required?	Weight per UOM [kg/UOM]
3/8" PEX Clip, 100/pkg.	F7060375	17.40	28.95	40.97	-	0.0068038936
1/2" PEX Clip, 100/pkg.	F7051258	17.40	28.95	42.56	-	0.0072574866
3/4" PEX Clip, 100/pkg.	F7057500	17.40	35.20	48.56	No	0.0081646724
1" PEX Clip, 50/pkg.	F7051001	17.40	44.95	55.93	No	0.013

Installation

Mount the PEX Clips to the underside of the subfloor in the joist cavity with the use of a drywall screw or nail. Secure the tubing to the clips at 36" intervals along the joist cavity. Refer to the Uponor Radiant Installation Handbook for additional information.

Related applications

Radiant Heating and Cooling Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517