

## PEX clips

### Project Information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

### Technical data

Material	Plastic
Prop 65 label required?	Yes

### Product Information and application use

Uponor PEX Clips are designed to suspend crosslinked polyethylene (PEX) tubing below the underside of a subfloor in a joist cavity installation.



Part name	Part no.	A [Inch]	B [Inch]	C [Inch]	Weight per UOM [lbs/UOM]
1" PEX Clip, 50/pkg.	F7051001	0.685	1.77	2.202	0.03
1/2" PEX Clip, 100/pkg.	F7051258	0.685	1.14	1.676	0.016
3/4" PEX Clip, 100/pkg.	F7057500	0.685	1.386	1.912	0.018
3/8" PEX Clip, 100/pkg.	F7060375	0.685	1.14	1.613	0.015

### Installation

Mount the PEX Clips to the underside of the subfloor in the joist cavity with the use of a drywall screw or nail. Secure the tubing to the clips at 36" intervals along the joist cavity. Refer to the Uponor Radiant Installation Handbook for additional information.

### Related applications

Radiant Heating and Cooling Systems

Codes	Standards	Listings
-	-	-

### Footnotes

### Contact information

-	<p>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</p>	<p>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</p>
---	--	--