

# ProPEX lead-free (LF) brass water heater adapters

Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data	
Material	Stainless Steel
Subcomponent Material	LF Brass
	Stainless Steel
End type 1	ProPEX 3/4"
End type 2	FNPT 3/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

## Product information and application use

The Uponor ProPEX® Lead-free Water Heater Adapter (stainless steel) connects 3/4" PEX to a water heater.<sup>1</sup>

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	Weight per UOM [lbs/UOM]
ProPEX LF Water Heater Adapter, 3/4" PEX LF Brass x 3/4" FIP x 18	LF2957575	18.902	0.945	17.53	1.25	1.125	0.9

Part name	Part no.	Codes	Standards	Listings
ProPEX lead-free (LF) brass water heater adapters	LF2957575	UPC IBC IRC IPC NPC of Canada UMC NSPC IMC	NSF-372 ASTM F877 ASTM F1960 CSA B137.5 NSF-61 NSF-14	IAPMO-ES ICC-ES-PMG cNSFus-pw-G U.P.Code

Installation	Related applications
Refer to the AquaPEX® Professional Plumbing Installation Guide for more information.	PEX-a Plumbing Systems

Footnotes	Contact information
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008  Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517