

ProPEX lead-free (LF) brass elbows (PEX and PEX)

| roject information | | |
|--------------------------------|-----------------|--|
| Job name: | Location: | |
| Engineer: | Date submitted: | |
| Contractor: | Submitted by: | |
| Manufacturer's representative: | Approved by: | |

Technical data

 Material
 LF Brass

 End type 1
 ProPEX 3/4"

 End type 2
 ProPEX 3/4"


Temp/pressure ratings 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar)

 $$200\ ^{\circ}F\ (93\ ^{\circ}C)$$ at 80 psi (5.5 bar) Prop 65 label required? Yes

Product information and application use

Uponor ProPEX® lead-free (LF) brass elbows are available for use in hot and cold domestic potable water systems, hydronic heating systems, all Uponor plumbing systems and in the AquaSAFETM residential fire safety systems. 1 Each end features the ProPEX fitting for connections to Wirsbo hePEXTM tubing or Uponor AquaPEX® tubing. This product is safe for direct burial in soil.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



| Part name | Part no. | Codes | Standards | Listings |
|--|-----------|--|--|---|
| ProPEX lead-free (LF) brass elbows (PEX and PEX) | LF4710750 | UPC IBC IRC IPC NPC of Canada UMC NSPC IMC | NSF-372 ASTM F877 ASTM F1960 CSA B137.5 UL 1821 NSF- 61 NSF-14 | IAPMO-ES cNSFus-pw-fs-G ICC-ES- PMG U.P.Code |

| | Installation | Related applications |
|---|--|--|
| | | PEX-a Plumbing Systems |
| | PEX tools and ProPEX rings (sold separately) are required for connecting the PEX tubing. Refer | Uponor Residential Fire Safety Systems |
| | to the AquaPEX professional plumbing installation guide, Radiant floor heating installation handbook | Radiant Heating and Cooling Systems |
| (| or the AquaSAFE residential fire sprinkler installation guide for additional information. | Permafrost Protection Systems |
| | | Turf Conditioning Systems |
| | | |

| Footnotes | Contact information | |
|-----------|------------------------|-------------------------|
| | Uponor Inc. | Uponor Ltd. |
| | 5925 148th Street West | 6510 Kennedy Road |
| | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 |
| | T 800.321.4739 | T 888.594.7726 |
| | F 952.891.2008 | F 800.638.9517 |