

ProPEX lead-free (LF) brass washing machine outlet boxes

| Project information | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

| Technical data | |
|-------------------------|---|
| Material | LF Brass |
| Subcomponent Material | Box: High-impact polystyrene |
| | Frame: High-impact polystyrene |
| | Support Brackets: High-impact polystyrene |
| | Valve: LF Brass |
| Prop 65 label required? | Yes |

Product information and application use

Uponor's ProPEX® Washing Machine Outlet Box comes with two ½" ProPEX hot and cold, color-coded, lead-free brass valves.¹ The valves may be mounted from the top or bottom. The four support brackets provide easy mounting between studs. The snap-on frame (included) accommodates up to 1" drywall.



Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

| Part name | Part no. | A [inch] | B [inch] | C [inch] | Weight per UOM [lbs/UOM] |
|---|-----------|----------|----------|----------|--------------------------|
| ProPEX Washing Machine Outlet Box, 1/2" LF Brass Valves | LF5930500 | 25.03 | 8.786 | 3.731 | 1.95 |

| Part name | Part no. | Codes | Standards | Listings |
|--|-----------|-----------------------|---|----------------------|
| ProPEX lead-free (LF) brass washing machine outlet boxes | LF5930500 | UPC IPC NPC of Canada | NSF-372 ASME A112.18.1 ASTM F877 ASTM F1960 CSA B125 CSA B137.5 NSF-61 NSF-14 | cNSFus-pw-G U.P.Code |

| Installation | Related applications |
|--|------------------------|
| Mount in wall cavity at the desired location (e.g., behind washing machine) using the supplied mounting brackets or directly to studs. For more information, refer to the AquaPEX® Professional Plumbing Installation Guide. | PEX-a Plumbing Systems |

| Footnotes | Contact information |
|-----------|---|
| - | <div>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</div> <div>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</div> |