

# ProPEX lead-free (LF) brass washing machine outlet boxes

## Project information

|                                |                 |
|--------------------------------|-----------------|
| Job name:                      | Location:       |
| Engineer:                      | Date submitted: |
| Contractor:                    | Submitted by:   |
| Manufacturer's representative: | Approved by:    |

## Technical data

|                         |  |
|-------------------------|--|
| Material                | LF Brass   |
| Subcomponent Material   | Box: High-impact polystyrene<br>Frame: High-impact polystyrene<br>Support Brackets: High-impact polystyrene<br>Valve: LF Brass |
| Prop 65 label required? | Yes  |

## Product information and application use

Uponor's ProPEX® Washing Machine Outlet Box comes with two 1/2" ProPEX hot and cold, color-coded, lead-free brass valves.<sup>1</sup> The valves may be mounted from the top or bottom. The four support brackets provide easy mounting between studs. The snap-on frame (included) accommodates up to 1" drywall.



Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

| Part name   | Part no.  | A [inch] | B [inch] | C [inch] | Weight per UOM [lbs/UOM] |
|---|-----------|----------|----------|----------|--------------------------|
| ProPEX Washing Machine Outlet Box, 1/2" LF Brass Valves | LF5930500 | 25.03    | 8.786    | 3.731    | 1.95                     |

| Part name  | Part no.  | Codes                 | Standards   | Listings             |
|--|-----------|-----------------------|---|----------------------|
| ProPEX lead-free (LF) brass washing machine outlet boxes | LF5930500 | UPC IPC NPC of Canada | NSF-372 ASME A112.18.1 ASTM F877 ASTM F1960 CSA B125 CSA B137.5 NSF-61 NSF-14 | cNSFus-pw-G U.P.Code |

## Installation

Mount in wall cavity at the desired location (e.g., behind washing machine) using the supplied mounting brackets or directly to studs. For more information, refer to the AquaPEX® Professional Plumbing Installation Guide.

## Related applications

PEX-a Plumbing Systems

## Footnotes

-

## Contact information

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517