

ProPEX lead-free (LF) brass fire sprinkler adapter elbows

Project information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-------------------------|--|
| Material | LF Brass |
| End type 2 | FNPT 1/2" |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |

Product information and application use

ProPEX® lead-free (LF) brass fire sprinkler adapter elbows are designed for use with 3/4" or 1" Uponor AquaPEX® tubing to connect fire sprinklers to the Uponor residential AquaSAFE™ fire safety system. Use Uponor ProPEX fittings for the connections.¹



| Part name | Part no. | End Type 1 |
|--|-----------|-------------|
| ProPEX LF Brass Fire Sprinkler Adapter Elbow, 3/4" PEX x 1/2" FNPT | LF7717550 | ProPEX 3/4" |
| ProPEX LF Brass Fire Sprinkler Adapter Elbow, 1" PEX x 1/2" FNPT | LF7711050 | ProPEX 1" |

| Part name | Part no. | Codes | Standards | Listings |
|---|----------|------------------------------------|---|--|
| ProPEX lead-free (LF) brass fire sprinkler adapter elbows | All | UPC IRC IPC NPC of Canada NSPC IMC | NSF-372 ASTM F877 NSF-359 ASTM F1960 CSA B137.5 UL 1821 NSF-61 NSF-14 | IAPMO-ES ICC-ES-PMG cNSFus-pw-G U.P.Code |

Installation

Use the appropriate Uponor ProPEX ring for the tubing. Install the elbow using the Fire Sprinkler Adapter Mounting Bracket (A7750700) and Fire Sprinkler Adapter Push-on Nut (F7000005). For more information, refer to the Uponor AquaSAFE system installation guide

Related applications

PEX-a Plumbing Systems
AquaSAFE™ Fire Safety Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517