## Commercial EP branch multi-port elbows

Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Engineered Polymer
ProPEX 1/2"
73 °F (23 °C) at 160 psi (11 bar)
180 °F (82 °C) at 100 psi (6.9 bar)
200 °F (93 °C) at 80 psi (5.5 bar)

## Product information and application use

Engineered polymer (EP) branch multi-port elbows feature an integrated  ${}^{3}_{4}$ " or 1" ProPEX® inlet with  ${}^{1}_{2}$ " ProPEX branch outlets. 1 The elbows are designed for commercial plumbing applications to eliminate the need for multiple connections. Product includes EP Mounting Clips (F7051250) with Phillips self-tapping screws.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding applicationspecific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Part name		Part no.	A [inch]	B [inch]	C [inch]	End Type 1	Weight per UOM [lbs/UOM]
3/4" EP Branch M clips	Multi-port Elbow, 8 (1/2") outlets with mounting	Q2087550	9.89	2.325	1.768	ProPEX 3/4"	0.39
1" EP Branch Mu clips	ulti-port Elbow, 10 (1/2") outlets with mounting	Q2101000	11.75	2.561	1.768	ProPEX 1"	0.47
Part name	Part no.	Codes		Standards		Listings	
Commercial EP branch mult elbows	i-port All	UPC IBC IRC Canada UMC		F877 ASTM F	LC S115 ASTM 1960 CSA B137.5 ULC E119/UL 263 NSF- NSF-14	IAPMO-ES HUD   PMG cNSFus- pw UL U.P.Code	

Installation	Related applications
The mounting clips feature self-tapping screws, which are appropriate for wood or metal studs. Simply attach the clips to the multi-port and fasten the clips to the mounting surface.	PEX-a Plumbing Systems
Eastrataa	Context information

	Uponor Inc.	Uponor Ltd.		
	5925 148th Street West	6510 Kennedy Road		
-	Apple Valley, MN 55124	Mississauga, ON L5T 2X4		
	T 800.321.4739	T 888.594.7726		
	F 952.891.2008	F 800.638.9517		