## EP branch opposing-port multi-port tees

Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:


Manufacturer's representative	e:	
Technical data		
Material	Engineered Polymer	
End type 1	ProPEX 3/4"	
End type 2	ProPEX 1/2"	
End type 3	ProPEX 1/2"	
End type 4	ProPEX 1/2"	
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)	
	180 °F (82 °C) at 100 psi (6.9 bar)	
	200 °F (93 °C) at 80 psi (5.5 bar)	



Prop 65 label required?

Engineered polymer (EP) branch opposing-port multi-port tees feature a ¾" ProPEX® inlet with opposing ½" ProPEX branch outlets.1 These are designed for a central location to facilitate piping in two directions.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	G [inch]	H [inch]	Weight per UOM [lbs/UOM]
3/4" EP Branch Opposing-port Multi-port Tee, 3 (1/2") outlets	Q2337550	0.141	0.955	0.625	1.25	0.467	0.719	2.373	1.18	0.07
3/4" EP Branch Opposing-port Multi-port Tee, 4 (1/2") outlets	Q2347550	3.58	0.955	0.625	1.25	0.467	0.719	2.373	1.18	0.07

Part name	Part no.	Codes	Standards	Listings
EP branch opposing-port multi-port tees	All	UPC IBC IRC IPC NPC of Canada UMC NSPC IMC	ASTM E814/ULC S115 ASTM F877 ASTM F1960 CSA B137.5 ULC S102.2 ASTM E119/UL 263 NSF/ANSI/CAN 61 ULC S101 NSF/ANSI 14	IAPMO-ES HUD MR 1269 ICC-ES- PMG cNSFus- pw UL U.P.Code cQAlus P321

Installation Related applications

Use any product designed to mount 1" copper pipe as a mounting bracket. For more information, refer to the Uponor Piping Systems Installation Guide.

PEX-a Plumbing Systems

Footnotes	Contact information			
	Uponor Inc.	Uponor Ltd.		
	5925 148th Street West	6510 Kennedy Road		
•	Apple Valley, MN 55124	Mississauga, ON L5T 2X4		
	T 800.321.4739	T 888.594.7726		
	F 952.891.2008	F 800.638.9517		