

## ProPEX brass sweat adapters

Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

## Technical data

Temp/pressure ratings 73 °F (23 °C) at 160 psi (11 bar)


180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

Prop 65 label required? Yes

## Product information and application use

ProPEX® brass sweat adapters transition Uponor PEX pipe to copper pipe for use in hydronic heating and cooling systems.1 One end of the adapter is manufactured with the Uponor ProPEX fitting for connection to Wirsbo hePEX™ pipe and the other end is manufactured to adapt copper sweat connections. These adapters are not safe for direct burial in soil. Note: Not for potable use.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Part name	Part no.	Cv	Material group	End Type 1	End Type 2
ProPEX LF Brass Sweat Adapter, 3/8" PEX x 1/2" Copper	LF4513850	5.7	LF Brass	ProPEX 3/8"	Sweat 1/2"
ProPEX Brass Sweat Adapter, 1/2" PEX x 1/2" Copper	Q5515050	5.7	Brass	ProPEX 1/2"	Sweat 1/2"
ProPEX LF Brass Sweat Adapter, 1/2" PEX x 3/4" Copper	LF4515075	5.1	LF Brass	ProPEX 1/2"	Sweat 3/4
ProPEX Brass Sweat Adapter, 5/8" PEX x 1/2" Copper	Q4516350	-	Brass	ProPEX 5/8"	Sweat 1/2
ProPEX Brass Sweat Adapter, 5/8" PEX x 3/4" Copper	Q4516375	-	Brass	ProPEX 5/8"	Sweat 3/4
ProPEX Brass Sweat Adapter, 3/4" PEX x 1/2" Copper	Q5517550	8.8	Brass	ProPEX 3/4"	Sweat 1/2
ProPEX Brass Sweat Adapter, 3/4" PEX x 3/4" Copper	Q5517575	13.4	Brass	ProPEX 3/4"	Sweat 3/4
ProPEX Brass Sweat Adapter, 3/4" PEX x 1" Copper	Q5517510	10.9	Brass	ProPEX 3/4"	Sweat 1"
ProPEX Brass Sweat Adapter, 1" PEX x 1" Copper	Q5511010	22.1	Brass	ProPEX 1"	Sweat 1
ProPEX Brass Sweat Adapter, 1 1/4" PEX x 1 1/4" Copper	Q5511313	34	Brass	ProPEX 1-1/4"	Sweat 1-1/
ProPEX Brass Sweat Adapter, 2" PEX x 2" Copper	Q5512020	83.6	Brass	ProPEX 2"	Sweat 2
ProPEX LF Brass Sweat Adapter, 3" PEX x 3" Copper	LF4513030	189.1	LF Brass	ProPEX 3"	Sweat 3
ProPEX Brass Sweat Adapter, 1 1/2" PEX x 1 1/2" Copper	Q5511515	45.5	Brass	ProPEX 1-1/2"	Sweat 1-1

Part name	Part no.	Codes	Standards	Listings			
ProPEX brass sweat adapters	All	IBC IRC NPC of Canada UMC IMC	ASTM F877 ASTM F1960 CSA B137.5 NSF-14	IAPMO-ES ICC-ES-PMG			
In addition, the following parts have additional codes, standards, or listings:							
ProPEX LF Brass Sweat Adapter, 3/8" PEX x 1/2" Copper	LF4513850	UPC IPC NSPC	NSF-372 NSF-61	cNSFus-pw-G U.P.Code			
ProPEX Brass Sweat Adapter, 1/2" PEX x 1/2" Copper	Q5515050			cNSFus-rfh			
ProPEX LF Brass Sweat Adapter, 1/2" PEX x 3/4" Copper	LF4515075	UPC IPC NSPC	NSF-372 NSF-61	cNSFus-pw-G U.P.Code			
ProPEX Brass Sweat Adapter, 5/8" PEX x 1/2" Copper	Q4516350			cNSFus-rfh			
ProPEX Brass Sweat Adapter, 5/8" PEX x 3/4" Copper	Q4516375			cNSFus-rfh			
ProPEX Brass Sweat Adapter, 3/4" PEX x 1/2" Copper	Q5517550			cNSFus-rfh			
ProPEX Brass Sweat Adapter, 3/4" PEX x 3/4" Copper	Q5517575			cNSFus-rfh			
ProPEX Brass Sweat Adapter, 3/4" PEX x 1" Copper	Q5517510			cNSFus-rfh			
ProPEX Brass Sweat Adapter, 1" PEX x 1" Copper	Q5511010			cNSFus-rfh			
ProPEX Brass Sweat Adapter, 1 1/4" PEX x 1 1/4" Copper	Q5511313			cNSFus-rfh			
ProPEX Brass Sweat Adapter, 2" PEX x 2" Copper	Q5512020			cNSFus-rfh			
ProPEX LF Brass Sweat Adapter, 3" PEX x 3" Copper	LF4513030	UPC IPC NSPC	NSF-372 NSF-61	cNSFus-pw-G U.P.Code			
ProPEX Brass Sweat Adapter, 1 1/2" PEX x 1 1/2" Copper	Q5511515			cNSFus-rfh			

Installation Related applications

Use the appropriate Uponor ProPEX ring for the pipe (sold separately). Do not solder within 18" of the ProPEX fitting. Refer to the Radiant Floor Heating Installation Handbook, Complete Design Assistance Manual (CDAM), or the Hydronic Piping Design Assistance Manual (HPDAM) for additional information.

Radiant Heating and Cooling Systems
Permafrost Protection Systems
Turf Conditioning Systems
Hydronic Piping Systems

Footnotes	Contact in	Contact information		
	Uponor Inc.	Uponor Ltd.		
	5925 148th Street West	6510 Kennedy Road		
•	Apple Valley, MN 55124	Mississauga, ON L5T 2X4		
	T 800.321.4739	T 888.594.7726		
	F 952.891.2008	F 800.638.9517		