

# ProPEX rings, blue

## Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

## Technical data

Material    PEX

## Product information and application use

Uponor ProPEX® rings are required to make a proper ProPEX connection.



Part name	Part no.	A [inch]	B [inch]	C [inch]	Inner diameter pipe [inch]	Outer diameter pipe [inch]	Weight per UOM [lbs/UOM]
ProPEX Ring, 1/2" Blue	Q4690504	0.862	0.862	0.63	0.633	0.879	0.01
ProPEX Ring, 3/4" Blue	Q4690754	1.114	1.114	0.866	0.882	1.128	0.01
ProPEX Ring, 1" Blue	Q4691004	1.406	1.406	1.102	1.134	1.42	0.02

Installation	Related applications
Square cut the Uponor PEX tubing. Remove excess material. Slide the ProPEX ring over the end of the tubing (maximum 1 /16" overhang for rings without stop). Expand the tubing and ring. If using the ProPEX Manual Expander Tool, rotate the tool a quarter turn after each expansion to prevent the formation of grooves. Remove the expansion tool and fully seat the tubing and ring against the shoulder of the fitting. Make ProPEX connections at temperatures above 5°F/-15°C. For more information, refer to the Uponor PEX Piping Systems Design and Installation Guide.	PEX-a Plumbing Systems

## Notes

Degree of crosslinking: 70% to 89%

Footnotes	Contact information
-	<div>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</div> <div>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</div>