

ProPEX EP 45 elbows

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:


Technical data

Material	Engineered Polymer
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)

Product information and application use

ProPEX® engineered polymer (EP) elbows make 45-degree connections for Uponor crosslinked polyethylene (PEX-a) tubing for use in hot and cold domestic potable water systems, residential fire safety and hydronic radiant heating and cooling systems. Each end of the elbow is manufactured with an Uponor ProPEX fitting for connections to Uponor AquaPEX® or Wirsbo hePEX™ tubing.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Part name	Part no.	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	Cv	End Type 1	End Type 2
ProPEX EP 45 Elbow, 1" PEX x 1" PEX	Q4761010	30.25	15.24	15.24	55.14	86.52	37.59	12.55	19.1	ProPEX 1"	ProPEX 1"
ProPEX EP 45 Elbow, 1 1/4" PEX x 1 1/4" PEX	Q4761313	36.96	15.24	15.24	65.18	100.09	46.23	15.58	29.7	ProPEX 1-1/4"	ProPEX 1-1/4"
ProPEX EP 45 Elbow, 1 1/2" PEX x 1 1/2" PEX	Q4761515	43.54	15.24	15.24	72.42	112.21	52.58	17.01	33.1	ProPEX 1-1/2"	ProPEX 1-1/2"
ProPEX EP 45 Elbow, 2" PEX x 2" PEX	Q4762020	54.79	19.05	19.05	95.68	143.10	71.63	23.89	68.9	ProPEX 2"	ProPEX 2"
ProPEX EP 45 Elbow, 2 1/2" PEX x 2 1/2" PEX	Q4762525	71.88	25.40	25.40	122.25	186.77	91.44	30.73	136.8	ProPEX 2-1/2"	ProPEX 2-1/2"
ProPEX EP 45 Elbow, 3" PEX x 3" PEX	Q4763030	85.85	27.94	27.94	144.27	219.02	106.68	36.83	195.5	ProPEX 3"	ProPEX 3"

Part name	Part no.	Weight per UOM [kg/UOM]
ProPEX EP 45 Elbow, 1" PEX x 1" PEX	Q4761010	0.028
ProPEX EP 45 Elbow, 1 1/4" PEX x 1 1/4" PEX	Q4761313	0.044
ProPEX EP 45 Elbow, 1 1/2" PEX x 1 1/2" PEX	Q4761515	0.059
ProPEX EP 45 Elbow, 2" PEX x 2" PEX	Q4762020	0.145
ProPEX EP 45 Elbow, 2 1/2" PEX x 2 1/2" PEX	Q4762525	0.295
ProPEX EP 45 Elbow, 3" PEX x 3" PEX	Q4763030	0.485

Part name	Part no.	Codes	Standards	Listings
ProPEX EP 45 elbows	All	IMC UPC IBC IRC IPC NPC of Canada UMC NSPC	ASTM F1960 ASTM E119/UL 263 ASTM E84 ASTM E814/ULC S115 ASTM F877 CSA B137.5 ULC S102.2 ULC S101	IAPMO-ES ICC-ES-PMG cNSFus-pw UL U.P.Code cQAlus P321 HUD MR 1269
In addition, the following parts have additional codes, standards, or listings:				
ProPEX EP 45 Elbow, 1" PEX x 1" PEX	Q4761010		NSF-61 NSF-14	
ProPEX EP 45 Elbow, 1 1/4" PEX x 1 1/4" PEX	Q4761313		NSF-61 NSF-14	
ProPEX EP 45 Elbow, 1 1/2" PEX x 1 1/2" PEX	Q4761515		NSF/ANSI CAN 61 NSF/ANSI 14	
ProPEX EP 45 Elbow, 2" PEX x 2" PEX	Q4762020		NSF/ANSI CAN 61 NSF/ANSI 14	
ProPEX EP 45 Elbow, 2 1/2" PEX x 2 1/2" PEX	Q4762525		NSF-61 NSF-14	
ProPEX EP 45 Elbow, 3" PEX x 3" PEX	Q4763030		NSF-61 NSF-14	
Installation		Related applications		
Use the appropriate ProPEX ring for PEX-a tubing. Refer to the Uponor PEX Piping Systems Design and Installation Manual for additional information.		PEX-a Plumbing Systems		
		Hydronic Radiant Heating and Cooling Systems		
		Turf Conditioning Systems		
		Permafrost Prevention Systems		
		AquaSAFE™ Fire Safety Systems		
Footnotes		Contact information		
-		Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008		
		Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517		