

ProPEX lead-free (LF) brass water meter valves

Project information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |


Technical data

| | |
|-------------------------|--|
| Material | LF Brass |
| Subcomponent Material | Valve: C27453 lead-free (LF) brass per ASTM B283/B283M Metal nut: UNS CW614 per ASTM B16/B16M EP nut: Polypropylene GF30 black Gasket: EPDM |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |

Product information and application use

Use Uponor ProPEX® lead-free (LF) brass water meter service valves in all commercial submetering and residential water service inlets, outlets or both.1 The valves allow for a direct ASTM F1960 connection to water meters sized 5/8" to 1". Valve is sized for 3/4" or 1" Uponor AquaPEX® tubing. Product handle material is stainless steel.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



| Part name | Part no. | Cv | End Type 1 | End Type 2 |
|--|-----------|------|-------------|-------------|
| ProPEX LF Brass Straight Water Meter Valve, 3/4" PEX x 1" NPSM | WS4820750 | 10.9 | ProPEX 3/4" | NPSM 1" |
| ProPEX LF Brass Straight Water Meter Valve, 1" PEX x 1 1/4" NPSM | WS4821000 | 18.7 | ProPEX 1" | NPSM 1-1/4" |
| ProPEX LF Brass Elbow Water Meter Valve, 3/4" PEX x 1" NPSM | WS4820751 | 4.9 | ProPEX 3/4" | NPSM 1" |
| ProPEX LF Brass Elbow Water Meter Valve, 1" PEX x 1 1/4" NPSM | WS4821001 | 9.7 | ProPEX 1" | NPSM 1-1/4" |

| Part name | Part no. | Codes | Standards | Listings |
|--|----------|--|---|----------------------------------|
| ProPEX lead-free (LF) brass water meter valves | All | UPC IBC IRC IPC NPC of Canada UMC NSPC IMC | NSF-372 ASTM F877 NSF-359 ASTM F1960 CSA B137.5 NSF-61 NSF-14 | HUD MR 1269 cNSFus-pw-G U.P.Code |

| Installation | Related applications |
|---|------------------------|
| ProPEX tool and ProPEX rings (sold separately) are required for connecting the PEX tubing. For more information, refer to the Uponor Residential Plumbing Systems Installation Guide or the Uponor Piping Systems Installation Guide. | PEX-a Plumbing Systems |

| Footnotes | Contact information |
|-----------|--|
| - | Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517 |