

End caps with vent

Project information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-------------------------|--|
| Material | Brass |
| Manifold size | 1 inch |
| End type 1 | ISO 228-G 1-1/4" |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |
| Max. fluid flow rate | 21 gpm |
| Prop 65 label required? | Yes |

Product information and application use

The End Cap with Vent, R32, caps the end of the TruFLOW™ Jr. modular manifolds. It comes complete with a swivel drain valve and a manual air vent. Includes required Manifold Gasket (A2403232).



| Part name | Part no. | A [mm] | B [mm] | C [mm] | Weight per UOM [kg/UOM] |
|------------------------|----------|--------|--------|--------|-------------------------|
| End Cap with Vent, R32 | A2803250 | 100 | 77.55 | 50 | 0.408 |

| Installation | Related applications |
|--------------|----------------------|
|--------------|----------------------|

Use with TruFLOW Jr. modular manifolds (not preassembled). Use the End Cap with Vent on the top manifold, following procedures outlined in the Uponor TruFLOW Jr. instruction sheet.

Radiant Heating and Cooling Systems

| Notes |
|-------|
|-------|

Connection:
1½" BSPP

| Footnotes | Contact information |
|-----------|---|
| - | <div>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</div> <div>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</div> |