End caps with vent

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Brass
Manifold size	1 inch
End type 1	ISO 228-G 1-1/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Max. fluid flow rate	21 gpm
Prop 65 label required?	Yes

Product information and application use

The End Cap with Vent, R32, caps the end of the TruFLOWTM Jr. modular manifolds. It comes complete with a swivel drain valve and a manual air vent. Includes required Manifold Gasket (A2403232).



Part name	Part no.	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]
End Cap with Vent, R32	A2803250	3.937	3.053	1.969	0.9

Installation

Use with TruFLOW Jr. modular manifolds (not preassembled). Use the End Cap with Vent on the top manifold, following procedures outlined in the Uponor TruFLOW Jr. instruction sheet.

Related applications

Radiant Heating and Cooling Systems

Notes

Connection:
1¼" BSPP

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2026 Uponor North America. All Rights Reserved