

ProPEX lead-free (LF) brass fire sprinkler adapter tees

| Project information | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

Material LF Brass End type 3 FNPT 1/2"

Temp/pressure ratings 73 °F (23 °C) at 160 psi (11 bar)

180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

Prop 65 label required? Yes

Product information and application use

Designed for use with 34 " or 1" Uponor AquaPEX® tubing, the ProPEX® Lead-free Brass Fire Sprinkler Adapter Tee connects fire sprinklers to the Uponor residential AquaSAFETM Looped multipurpose fire safety system, which combines fire sprinklers with a home's potable cold-water plumbing system. Use Uponor ProPEX fittings for the connections.



| Part name | Part no. | A [mm] | B [mm] | C [mm] | D [mm] | E [mm] | F [mm] | G [mm] | H [mm] | l [mm] | End Type 1 |
|---|--------------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|------------------|
| ProPEX LF Brass Fire Sprinkler Adapter Tee, 3/4 3/4" PEX x 1/2" FNPT | PEX x LF7707575 | 24 | 21.97 | 21.97 | 24 | 14.22 | 27.66 | 91.95 | 56.11 | 37.08 | ProPEX 3/4" |
| ProPEX LF Brass Fire Sprinkler Adapter Tee, 1" PEX x 1/2" FNPT | PEX x 1" LF7701010 | 30 | 21.97 | 21.97 | 30 | 14.22 | 27.66 | 103.94 | 56.11 | 37.08 | ProPEX 1" |

| Part name | Part no. | End Type 2 | Weight per UOM [kg/UOM] |
|---|-----------|-------------|-------------------------|
| ProPEX LF Brass Fire Sprinkler Adapter Tee, 3/4" PEX x 3/4" PEX x 1/2" FNPT | LF7707575 | ProPEX 3/4" | 0.281 |
| ProPEX LF Brass Fire Sprinkler Adapter Tee, 1" PEX x 1" PEX x 1/2" FNPT | LF7701010 | ProPEX 1" | 0.281 |

| Part name | Part no. | Codes | Standards | Listings |
|---|----------|--|--|--|
| ProPEX lead-free (LF) brass fire sprinkler adapter tees | All | UPC IBC IRC IPC NPC of Canada UMC NSPC IMC | NSF-372 ASTM F877 ASTM F1960 CSA B137.5 UL 1821 NSF- 61 NSF-14 | cNSFus-pw-fs-G ICC-ES- PMG U.P.Code |

Installation Related applications

Use the appropriate Uponor ProPEX Ring for the tubing. Install the tee using the Fire Sprinkler Adapter Mounting Bracket (A7750700) and Fire Sprinkler Adapter Push-on Nut (F7000005). For more information, refer to the Uponor AquaSAFE Looped System Installation Guide.

PEX-a Plumbing Systems

AquaSAFE™ Fire Safety Systems

| Footnotes | Contr | Contact information | | | |
|-----------|------------------------|-------------------------|--|--|--|
| | Uponor Inc. | Uponor Ltd. | | | |
| | 5925 148th Street West | 6510 Kennedy Road | | | |
| - | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 | | | |
| | T 800.321.4739 | T 888.594.7726 | | | |
| | F 952.891.2008 | F 800.638.9517 | | | |