

ProPEX lead-free (LF) brass ice maker boxes

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Stainless Steel
End type 1	ProPEX 1/2"
End type 2	Compression 1/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes



Product information and application use

The ProPEX® Ice Maker Box with Support Brackets, 1/2" (LF Brass) Valve with snap-in frame includes a 1/2" lead-free brass valve with 1/4" O.D. compression connection.1 This high-impact box is an aesthetic, convenient option for connecting to standard ice maker tubing. Two support brackets are provided for easy mounting.

Part name	Part no.	A [Inch]	B [Inch]	C [Inch]	Weight per UOM [lbs/UOM]
1/4" Insert (stainless steel)	F5400250	0.719	0.323	0.323	0
ProPEX Ice Maker Box with Support Brackets, 1/2" LF Brass Valve	LF5955025	20.29	6	3.55	0.87

Installation

Mount in wall cavity at the desired location (e.g., behind refrigerator) using the supplied mounting brackets or directly to studs. For more information, refer to the AquaPEX® Professional Plumbing Installation Guide.

Related applications

PEX-a Plumbing Systems

Codes

UPC|IPC|NPC of Canada

Standards

NSF-372|ASME A112.18.1|ASTM F877|ASTM F1960|CSA B125|CSA B137.5|NSF-61|NSF-14

Listings

cNSFus-pw-G|U.P.Code

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517