## ProPEX lead-free (LF) brass washing machine outlet boxes

Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

## Technical data

Material LF Brass

Subcomponent Material Box: High-impact polystyrene

Frame: High-impact polystyrene

Support Brackets: High-impact polystyrene

Valve: LF Brass

Prop 65 label required? Yes

## Product information and application use

Uponor's ProPEX® Washing Machine Outlet Box comes with two ½" ProPEX hot and cold, color-coded, lead-free brass valves.1 The valves may be mounted from the top or bottom. The four support brackets provide easy mounting between studs. The snap-on frame (included) accommodates up to 1" drywall.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Part name	Part no.	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]
ProPEX Washing Machine Outlet Box, 1/2" LF Brass Valves	LF5930500	25.03	8.786	3.731	1.95

Part name	Part no.	Codes	Standards	Listings
ProPEX lead-free (LF) brass washing machine outlet boxes	LF5930500	UPC IPC NPC of Canada	NSF-372 ASME A112.18.1 ASTM F877 ASTM F1960 CSA B125 CSA B137.5 NSF-61 NSF-14	cNSFus-pw-G U.P.Code

## stallation Related applications

Mount in wall cavity at the desired location (e.g., behind washing machine) using the supplied mounting brackets or directly to studs. For more information, refer to the AquaPEX® Professional Plumbing Installation Guide.

PEX-a Plumbing Systems

Footnotes	Contact ir	Contact information		
	Uponor Inc.	Uponor Ltd.		
	5925 148th Street West	6510 Kennedy Road		
•	Apple Valley, MN 55124	Mississauga, ON L5T 2X4		
	T 800.321.4739	T 888.594.7726		
	F 952.891.2008	F 800.638.9517		