Radiant Rollout Mats

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Product information and application use

The Radiant RolloutTM Mat features ½" or ⅝" Wirsbo hePEXTM tubing that has an oxygen-diffusion barrier that meets German DIN 4726/9. The mat can include a ¾" reverse-return header with ¾" ProPEX EP fittings that is pressurized to 20 psi to ensure system integrity. The mat can also be designed without a reverse-return header. In this instance, it is not prepressurized and can connect to a wall manifold such as the TruFLOW™ Classic Manifold



Installation

At the jobsite, roll out the mat and, depending on your header/manifold selection, connect to a supply-and-return line using the attached header (optional) or connect each loop to a wall manifold (optional). Contact your local Uponor representative for more information.

Related applications

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2026 Uponor North America. All Rights Reserved