

# Slab sensor 10k

## Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

## Technical data

Prop 65 label required? Yes

## Product information and application use

Slab sensors read temperature conditions to provide feedback and information to temperature control devices



Part name	Part no.	Weight per UOM [lbs/UOM]
Slab Sensor, 10k	A9010599	0.3

Installation	Related applications
Fasten the terminal connectors on the back of the thermostat. For more information, refer to the manuals for the Uponor Heat-only Thermostat with Touchscreen (A3100101) and the Uponor Wireless Digital Thermostat (A3800167)	<ul style="list-style-type: none"> <li>Radiant heating systems</li> <li>Permafrost Protection Systems</li> <li>Turf Conditioning Systems</li> </ul>

Codes	Standards	Listings
-	-	-

## Notes

Ambient conditions:  
 10% to 90% humidity (non-condensing)  
 Sensor type: 10k J-curve  
 Tolerance: +/- 1% at 77°F (25°C)  
 Wire type: 22 gauge  
 IP68 continuous immersion 3m /10 ft

Footnotes	Contact information		
-	<table border="0"> <tr> <td>           Uponor Inc.            5925 148th Street West            Apple Valley, MN 55124            T 800.321.4739            F 952.891.2008         </td> <td>           Uponor Ltd.            6510 Kennedy Road            Mississauga, ON L5T 2X4            T 888.594.7726            F 800.638.9517         </td> </tr> </table>	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517		