Threaded brass manifold straight adapters and bushings


U		n	
	Μ		

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

l echnical data	
End type 1	ISO 228-G 1-1/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

Product information and application use

Uponor's Threaded Brass Manifold Bushings are used in TruFLOWTM manifolds. In radiant heating applications, the bushing transitions the R32 manifold union nut to 1" national pipe thread (NPT) and $\frac{3}{4}$ " threaded connections (PEX or Multi-layer Composite (MLC) tubing with QS-style fittings).



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	Material group	End Type 2	E [inch]	F [inch]	G [inch]	H [inch]
Threaded Brass Manifold Straight Adapter, R32 Male x R20 Male	A4143220	0.635	0.35	0.599	2.02	Brass	ISO 228-G 3/4"	1.584	1.75	1.01	0.875
Threaded Brass Manifold Straight Adapter, R32 Male x R25 Male	A4143225	0.613	0.35	0.635	2.02	LF Brass	ISO 228-G 1"	1.598	1.75	1.01	0.875
Threaded Brass Manifold Bushing, R32 Male x 3/4" Female NPT	A2133275	2.018	1.75	0.985	-	Brass	FNPT 3/4"	-	-	-	-
Threaded Brass Manifold Bushing, R32 Male x 1" Female NPT	A2123210	1.918	1.687	0.985	1	Brass	FNPT 1"	-	-	-	-

Part name	Part no.	Weight per UOM [lbs/UOM]
Threaded Brass Manifold Straight Adapter, R32 Male x R20 Male	A4143220	0.55
Threaded Brass Manifold Straight Adapter, R32 Male x R25 Male	A4143225	0.5
Threaded Brass Manifold Bushing, R32 Male x 3/4" Female NPT	A2133275	0.44
Threaded Brass Manifold Bushing, R32 Male x 1" Female NPT	A2123210	0.3

Part name	Part no.	Codes	Standards	Listings		
Threaded brass manifold straight adapters and bushings	All	IMC IRC NBC of Canada	UMC CSA B137.5 R32: ISO 228-G 1¼" ASTM F877	cNSFus-rfh		
Installation		Rei	ated applications			
			Radiant Heating and Cooling Systems			
Thread directly into Uponor TruFLOW manifolds. For additional information, refer to the TruFLOW Manifold Instruction Sheet or the Uponor Radiant Floor Heating Installation Handbook.		. Per	Permafrost Protection Systems			

Turf Conditioning Systems

Footnotes	Contact i	Contact information		
	Uponor Inc.	Uponor Ltd.		
	5925 148th Street West	6510 Kennedy Road		
	Apple Valley, MN 55124	Mississauga, ON L5T 2X4		
	T 800.321.4739	T 888.594.7726		
	F 952.891.2008	F 800.638.9517		