

Three-way mixing valves

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Subcomponent Material	Brass Brass (chrome-plated) Modified Teflon® Ethylene propylenediene monomer(EPDM) rubber
Ambient humidity non-condensing max [%]	90
Prop 65 label required?	Yes



Product information and application use

N/A

Part name	Part no.	A [inch]	B [inch]	C [inch]	Operating voltage AC [VAC]	Weight per UOM [lbs/UOM]
3/4" Three-way Mixing Valve, (CV=4.5)	A3040075	4.702	4.383	2.42	24	1.5
1" Three-way Mixing Valve, (CV=4.5)	A3040100	4.702	4.383	2.42	24	-

Part name	Part no.	Codes	Standards	Listings
Three-way mixing valves	All	-	Class II wiring	-

Installation

N/A

Related applications

-

Notes

3/4" Cv=4.5
Service:
Closed-system hot and cold water
Maximum 50% glycol

1" Cv=4.5
Service:
Closed-system hot and cold water
Maximum 50% glycol
Maximum operating pressure: 300 psi (2,100 kPa)
Maximum shutoff pressure: 125 psi (875 kPa)

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517