

Tube clamps

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Plastic
Subcomponent Material	Polypropylene (PP)

Product information and application use

Tube Clamps secure 1/2" and 3/4" Uponor crosslinked polyethylene (PEX-a) tubing products.



Part name	Part no.	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]
Tube Clamp Suspension (1/2 PEX), 100/pkg.	A7250500	2	1.407	0.75	0.01
Tube Clamp Suspension (3/4 PEX), 50/pkg.	A7250750	2	1.672	0.75	0.01
Tube Clamp Standard (1/2 PEX), 100/pkg.	A7350500	2	0.86	0.687	0.02
Tube Clamp Standard (3/4 PEX), 50/pkg.	A7350750	2.375	1.125	0.687	0.02

Installation

Fasten the tube clamp onto the tubing mounting surface. Refer to the Uponor Radiant Floor Installation Handbook or the Uponor Professional Plumbing Installation Guide for additional information

Related applications

Radiant Heating and Cooling Systems
Permafrost Protection Systems
Turf Conditioning Systems
PEX-a Plumbing Systems
AquaSAFE™ Fire Safety Systems

Footnotes

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517