

## Two-wire thermal actuators for Stainless-steel Manifolds

eject information		
Job name:	Location:	
Engineer:	Date submitted:	
Contractor:	Submitted by:	
Manufacturer's representative:	Approved by:	

## Technical data

Prop 65 label required? Yes

Product information and application use

The Uponor Two-wire Thermal Actuators are slow-opening thermal actuators that mount directly onto Uponor manifolds. They provide individual-loop flow control on multi-zoned manifolds.





Part name Part name		Part no.	Current draw max. [A]	Operating voltage AC [VAC]	
	Two-wire Thermal Actuator for Stainless-steel Manifolds		A3030524 0.083		24
F	Part name	Part no.	Codes	Standards	Listings

Part name	Part no.	Codes	Standards	Listings
Two-wire thermal actuators for Stainless-steel Manifolds	A3030524	-	Class II wiring	-

Inst	tallation	Related applications
		Radiant Heating and Cooling Systems
Mo	ount directly onto the manifold. Refer to the manifold installation guide for detailed instructions.	Permafrost Protection Systems
		Turf Conditioning Systems

## Notes

Time to Open/Close:

3 to 5 minutes

Footnotes	Contact information	
	Uponor Inc.	Uponor Ltd.
	5925 148th Street West	6510 Kennedy Road
•	Apple Valley, MN 55124	Mississauga, ON L5T 2X4
	T 800.321.4739	T 888.594.7726
	F 952.891.2008	F 800.638.9517