Two-wire thermal actuators for TruFLOW Classic and Jr. Valved Manifolds

uponor

Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:
Technical data	

Prop 65 label required? Yes

Product information and application use

The Uponor Two-wire Thermal Actuators are slow-opening thermal actuators that mount directly onto Uponor manifolds. They provide individual-loop flow control on multi-zoned manifolds.

Part name		Part no.	Current draw max. [A]	Operating voltage AC [VAC]
Two-wire Thermal Actuator Valved Manifolds	r for TruFLOW Classic and Jr.	A3030523	0.083	24
Part name	Part no.	Codes	Standards	Listings
Two-wire thermal actuators for TruFLOW Classic and Jr. Valved Manifolds	A3030523		Class II wiring	-
Installation Related applications				

Mount directly onto the manifold. Refer to the manifold installation guide for detailed instructions.

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

Notes

Time to Open/Close: 3 to 5 minutes

Footnotes	Contact in	Contact information	
	Uponor Inc.	Uponor Ltd.	
	5925 148th Street West	6510 Kennedy Road	
-	Apple Valley, MN 55124	Mississauga, ON L5T 2X4	
	T 800.321.4739	T 888.594.7726	
	F 952.891.2008	F 800.638.9517	