

# Two-wire thermal actuators for TruFLOW Classic and Jr. Valved Manifolds



## Project information


Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

## Technical data

Prop 65 label required? Yes

## Product information and application use

The Uponor Two-wire Thermal Actuators are slow-opening thermal actuators that mount directly onto Uponor manifolds. They provide individual-loop flow control on multi-zoned manifolds.



Part name	Part no.	A [mm]	B [mm]	C [mm]	Current draw max. [A]	Operating voltage AC [VAC]	Weight per UOM [kg/UOM]
Two-wire Thermal Actuator for TruFLOW Classic and Jr. Valved Manifolds	A3030523	72.64	39.62	39.62	0.083	24	0.1134

Part name	Part no.	Codes	Standards	Listings
Two-wire thermal actuators for TruFLOW Classic and Jr. Valved Manifolds	A3030523	-	Class II wiring	-

## Installation

## Related applications

Mount directly onto the manifold. Refer to the manifold installation guide for detailed instructions.

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

## Notes

Time to Open/Close:  
3 to 5 minutes

Footnotes	Contact information
-	<div>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</div> <div>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</div>