

Two-wire thermal actuators for TruFLOW Classic and Jr. Valved Manifolds



Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Prop 65 label required? Yes

Product information and application use

The Uponor Two-wire Thermal Actuators are slow-opening thermal actuators that mount directly onto Uponor manifolds. They provide individual-loop flow control on multi-zoned manifolds.



Part name	Part no.	A [inch]	B [inch]	C [inch]	Current draw max. [A]	Operating voltage AC [VAC]	Weight per UOM [lbs/UOM]
Two-wire Thermal Actuator for TruFLOW Classic and Jr. Valved Manifolds	A3030523	2.86	1.56	1.56	0.083	24	0.25

Part name	Part no.	Codes	Standards	Listings
Two-wire thermal actuators for TruFLOW Classic and Jr. Valved Manifolds	A3030523	-	Class II wiring	-

Installation

Related applications

Mount directly onto the manifold. Refer to the manifold installation guide for detailed instructions.

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Notes

Time to Open/Close:
3 to 5 minutes

Footnotes

Contact information

-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
---	---	---