
Smatrix Pulse antenna (A-265), replacement parts

uponor

Floject mornation	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:
Technical data	

Operating temperature min. [°F]	32 °f
Operating temperature max. [°F]	113 °f
Ambient temperature min. [F]	-4 °f
Ambient temperature max. [F]	158 °f
Ambient humidity non-condensing max [%]	85
Prop 65 label required?	Yes
Product information and application use	
Use the Smatrix Pulse Antenna (A-265) repla Smatrix Pulse Controller with Antenna. Smatr floor heating as well as forced-air heating and Smatrix Pulse Controller (X-265) with Antenna	cement part to replace the antenna in the A380265A ix Pulse provides precise wireless control of radiant l cooling systems in one solution. The A380265A a (A-265) connects up to six (6) thermostats and eight lators, which, in turn, affect the flow of the supply water

system parameters.



ETHERNET CABLE LENGTH NOT TO SCALE

Part name		Ра	Part no.		Operating voltage AC [VAC]	
Smatrix Pulse Antenna (A-	-265), replacement part	A:	3801265		115	
Part name	Part no.	Codes	Stand	lards	Listings	
Smatrix Pulse antenna (A-265), replacement parts	A3801265			SS-210 ICC RSS-Gen FCC 47 Part 15	IC 7664A-SM4NA0 FCC ID V9MSM4NA0	
Installation			Related applications			
			Radiant			
Refer to the Smatrix Pulse Installation and Operation Manual for installation information.		ation information.	Hydronic Heating & Cooling	J		
			Tools & Accessories			
Footnotes				Contact information		

Footnotes	Contact information		
	Uponor Inc.	Uponor Ltd.	
	5925 148th Street West	6510 Kennedy Road	
	Apple Valley, MN 55124	Mississauga, ON L5T 2X4	
	T 800.321.4739	T 888.594.7726	
	F 952.891.2008	F 800.638.9517	