

ProPEX lead-free (LF) brass straight stop valves

| Project information | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

 Material
 LF Brass

 End type 1
 ProPEX 1/2"

 End type 2
 UNEF 3/8"


Temp/pressure ratings 194 °F (90 °C) at 145 psi (10 bar)

Prop 65 label required? Yes

Product information and application use

For point-of-use shutoff at the fixture, ProPEX® straight and angle stop valves are lead-free (LF) brass, chrome-plated, quarter-turn ball valves that feature an ASTM F1960 connection for 1/2" Uponor AquaPEX® pipe and a 3/8" male threaded connection for fixture risers.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



| Part name | Part no. | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | G [inch] | Weight per UOM [lbs/UOM] |
|---|-----------|----------|----------|-------------|-------------|----------|----------|-------------|--------------------------------|
| ProPEX LF Brass Straight Stop Valve, 1/2" PEX x 3/8" OD Comp. | LF5865038 | 2.067 | 1.388 | 0.7 | 0.709 | 0.433 | 0.433 | 1.417 | 0.15 |

| Part name | Part no. | Codes | Standards | Listings |
|--|-----------|--|---|----------------------|
| ProPEX lead-free (LF) brass straight stop valves | LF5865038 | UPC IBC IRC IPC NPC of Canada UMC NSPC IMC | ASME A112.18.1 NSF/ANSI/CAN 372 ASTM F877 ASTM F1960 CSA B125 CSA B137.5 NSF/ANSI/CAN 61 NSF/ANSI 14 | cNSFus-pw-G U.P.Code |

Installation Related applications

Install valves according to local building code. Do not dismantle. Refer to the Uponor PEX Piping Systems Design and Installation Manual or Uponor PEX Piping Systems Installation Guide for additional information. For rigid fixture riser connections, use the Uponor %" OD Compression Nut and Nylon Sleeve (part number F5440380), sold separately.

PEX-a Plumbing Systems

| Footnotes | Contact information | | |
|-----------|------------------------|-------------------------|--|
| | Uponor Inc. | Uponor Ltd. | |
| | 5925 148th Street West | 6510 Kennedy Road | |
| • | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 | |
| | T 800.321.4739 | T 888.594.7726 | |
| | F 952.891.2008 | F 800.638.9517 | |