

ProPEX rings, blue

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material PEX

Product information and application use

Uponor ProPEX® rings are required to make a proper ProPEX connection.



Part name	Part no.	A [Inch]	B [Inch]	C [Inch]	Inner diameter pipe [Inch]	Outer diameter pipe [Inch]	Weight per UOM [lbs/UOM]
ProPEX Ring, 1/2" Blue	Q4690504	0.862	0.862	0.63	0.633	0.879	0.01
ProPEX Ring, 3/4" Blue	Q4690754	1.114	1.114	0.866	0.882	1.128	0.01
ProPEX Ring, 1" Blue	Q4691004	1.406	1.406	1.102	1.134	1.42	0.02

Installation

Square cut the Uponor PEX tubing. Remove excess material. Slide the ProPEX ring over the end of the tubing (maximum 1/16" overhang for rings without stop). Expand the tubing and ring. If using the ProPEX Manual Expander Tool, rotate the tool a quarter turn after each expansion to prevent the formation of grooves. Remove the expansion tool and fully seat the tubing and ring against the shoulder of the fitting. Make ProPEX connections at temperatures above 5°F/-15°C. For more information, refer to the Uponor PEX Piping Systems Design and Installation Guide.

Related applications

PEX-a Plumbing Systems

Notes

Degree of crosslinking: 70% to 89%

Footnotes

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517