

ProPEX lead-free (LF) brass transition ball valve - Copper Press



Project Information


Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	LF Brass
Cold working pressure	250 psi
Temp/pressure ratings	200 °F (93 °C) at 200 psi (13.8 bar)
Prop 65 label required?	Yes

Product information and application use

These full-port ball valves with stainless-steel stems provide reliable, high-flow performance and allow contractors to speed installations in tight spaces for greater jobsite productivity while offering engineers optimal hybrid design opportunities to meet pressure, temperature, and space requirements.



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	G [inch]	H [inch]	I [inch]	J [inch]
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 1/2" PEX x 1/2" Copper Press	LFT4925050SS	2.469	0.974	2.064	4.72	3.425	0.465	1.583	0.38	0.709	1.012
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 3/4" PEX x 3/4" Copper Press	LFT4927575SS	2.972	1.279	2.415	4.929	3.425	0.524	1.791	0.511	0.945	1.122
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 1" PEX x 1" Copper Press	LFT4921010SS	3.539	1.508	2.99	6.22	4.547	0.685	2.236	0.635	1.181	1.453
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 1 1/4" PEX x 1 1/4" Copper Press	LFT4921313SS	4.26	1.856	3.171	6.541	4.547	0.821	2.396	0.775	1.445	1.791
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 1 1/2" PEX x 1 1/2" Copper Press	LFT4921515SS	5.138	2.118	4.15	8.091	5.638	0.98	3.091	0.907	1.705	2.124
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 2" PEX x 2" Copper Press	LFT4922020SS	6.28	2.823	4.78	8.65	5.638	1.122	3.362	1.159	2.146	2.559
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 2 1/2" PEX x 2 1/2" Copper Press	LFT4922525SS	7.945	3.956	6.578	13.121	9.508	1.543	4.619	1.584	2.79	3.159
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 3" PEX x 3" Copper Press	LFT4923030SS	9.207	4.606	7.287	13.485	9.508	1.89	4.984	1.844	3.34	3.669

Part name	Part no.	Cv	End Type 1	End Type 2	Weight per UOM [lbs/UOM]
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 1/2" PEX x 1/2" Copper Press	LFT4925050SS	5.5	ProPEX 1/2"	Copper Press 1/2"	0.33
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 3/4" PEX x 3/4" Copper Press	LFT4927575SS	12.6	ProPEX 3/4"	Copper Press 3/4"	0.49
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 1" PEX x 1" Copper Press	LFT4921010SS	22.8	ProPEX 1"	Copper Press 1"	0.84
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 1 1/4" PEX x 1 1/4" Copper Press	LFT4921313SS	31.8	ProPEX 1-1/4"	Copper Press 1-1/4"	1.26
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 1 1/2" PEX x 1 1/2" Copper Press	LFT4921515SS	41.8	ProPEX 1-1/2"	Copper Press 1-1/2"	1.99
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 2" PEX x 2" Copper Press	LFT4922020SS	67.3	ProPEX 2"	Copper Press 2"	3.17
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 2 1/2" PEX x 2 1/2" Copper Press	LFT4922525SS	110.9	ProPEX 2-1/2"	Copper Press 2-1/2"	7.82
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 3" PEX x 3" Copper Press	LFT4923030SS	187.2	ProPEX 3"	Copper Press 3"	10.14

Part name	Part no.	Codes	Standards	Listings
ProPEX lead-free (LF) brass transition ball valve - Copper Press	All	UPC IBC IRC IPC NPC of Canada UMC IMC	ASME B16.51 ASTM F877 NSF/ANSI/CAN 372 NSF/ANSI 359 ICC-ES LC1002 ASTM F1960 CSA B137.5 NSF/ANSI/CAN 61 NSF/ANSI 14	cNSFus-pw-G U.P.Code ICC-PMG-1412

In addition, the following parts have additional codes, standards, or listings:

ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 1/2" PEX x 1/2" Copper Press	LFT4925050SS			
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 1 1/4" PEX x 1 1/4" Copper Press	LFT4921313SS			
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 1 1/2" PEX x 1 1/2" Copper Press	LFT4921515SS			
ProPEX LF Brass Transition Ball Valve (full port) SS Ball and Stem 2" PEX x 2" Copper Press	LFT4922020SS			

Installation	Related applications
Use ProPEX LF brass transition ball valves for threaded, press, and flange connections in domestic water and mechanical HVAC piping applications.	-

Footnotes	Contact information
-	<p>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</p> <p>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</p>