

# Ecoflex thermal twin coils

## Project Information

Job name :	Location :
Engineer :	Date submitted:
Contractor :	Submitted by:
Manufacturer's representative :	Approved by :

## Technical data

Material	PEX
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

## Product Information and application use

Uponor's Ecoflex® Thermal Twin is a pre-insulated pipe system for buried or aboveground commercial and residential hydronic heating and cooling applications. Service pipes are made from durable Engel-method crosslinked polyethylene (PEX-a) tubing, protected by multilayer PEX-foam insulation and covered by a corrugated, waterproof HDPE jacket. Use with Uponor ProPEX® fittings or WIPEX™ dezincification-resistant (DZR) brass compression fittings. 1



Part name	Part no.	Inner diameter coil [inch]	Outer diameter coil [inch]	Coil width [inch]	Inner diameter pipe [inch]	Outer diameter pipe [inch]	Weight per UOM [lbs/UOM]
1 1/4" Thermal Twin Jr. with 5.5" Jacket, 600-ft. coil	5025513	5.5	12	5.5	1.054	1.375	1.28
1" Thermal Twin with 6.9" Jacket, 600-ft. coil	5026910	6.9	12	6.9	0.862	1.125	1.3
1 1/4" Thermal Twin with 6.9" Jacket, 500-ft. coil	5026913	6.9	12	6.9	1.054	1.375	1.4
1 1/2" Thermal Twin with 6.9" Jacket, 300-ft. coil	5026915	6.9	12	6.9	1.244	1.625	1.55
2" Thermal Twin with 7.9" Jacket, 300-ft. coil	5027920	7.9	12	7.9	1.629	2.125	2.68
2 1/2" Thermal Twin with 7.9" Jacket, 300-ft. coil	5027925	7.9	12	7.9	2.011	2.625	3.4

## Installation

Install Ecoflex Thermal Twin pre-insulated pipe in buried or aboveground hydronic heating and cooling applications. Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination. For more information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual.

## Related applications

- Pre-Insulated Pipe Systems
- Hydronic Heating and Cooling Systems
- Radiant Heating and Cooling Systems
- Permafrost Prevention Systems
- Turf Conditioning Systems
- AquaSAFE™ Fire Safety Systems

## Codes

UPC|IPC|NPC of Canada|UMC|NSPC|IMC

## Standards

ASTM F877|ASTM F1960|CSA B137.5|ASTM F876|NSF-61|ASTM F876|NSF-14

## Listings

cNSFus-pw|cNSFus-rfh|U.P.Code

## Footnotes

-

## Contact information

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.636.9517