

# Single EPDM rubber end caps

Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

## Technical data

Subcomponent Material

Rubber End Cap: EPDM (ethylene propylene diene monomer) rubber; Clamp Device: Stainless steel; O-ring: EPDM rubber

## Product information and application use

Use the EPDM Rubber End Cap to seal the exposed insulation between the jacket and service pipe when cutting pipe to make a connection. Designed to support system integrity, Ecoflex® End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination.



Part name	Part no.	Weight per UOM [kg/UOM]
End Cap, 3/4" and 1" Pipe with 2.7" Jacket	5852710	0.181
End Cap, 1" and 1 1/4" PEX Pipe with 5.5" Jacket	5855513	0.454
End Cap, 1 1/4", 1 1/2" and 2" HDPE Pipe with 5.5" Jacket	5855520	0.454
End Cap, 1 1/2", 2", 2 1/2" PEX and 3" HDPE Pipe with 6.9" Jacket	5856930	0.454
End Cap 3, 3 1/2, 4" PEX and 4" HDPE pipe, 7.9" Jacket	5857940	0.862

# Installation Related applications

The End Cap includes an O-ring and clamp device for a water-tight installation. Slip the End Cap on the jacket pipe and ensure that the O-ring stays in place. Refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual for more information.

Pre-Insulated Pipe Systems
Radiant Heating and Cooling Systems
Permafrost Prevention Systems
Turf Conditioning Systems

## Notes

Compatible Pipes 5012775; 5012710; 5212775; 5212710

Compatible Pipes 5015510; 5015513; 5215510; 5215513

Compatible Pipes 5115513; 5115515; 5115520

Compatible Pipes: 5016915; 5016920; 5016925; 5116930; 5216915; 5216920

Compatible Pipes: 5017930; 5017935; 5017940; 5117940; 5217930

Footnotes	Contact information	
	Uponor Inc.	Uponor Ltd.
	5925 148th Street West	6510 Kennedy Road
	Apple Valley, MN 55124	Mississauga, ON L5T 2X4
	T 800.321.4739	T 888.594.7726
	F 952.891.2008	F 800.638.9517