

Ecoflex potable PEX plus accessories

Project information

| | |
|---------------------------------|-----------------|
| Job name : | Location : |
| Engineer : | Date submitted: |
| Contractor : | Submitted by: |
| Manufacturer's representative : | Approved by : |

Technical data

Material Body: polyamide; conductors: nickel-coated brass

Product information and application use

Uponor heat-trace end seal is part of a universal power termination and splicing system for Uponor Ecoflex® potable PEX plus pre-insulated piping systems.



| Part name | Part no. | Weight per UOM [lbs/UOM] |
|---------------------------------|----------|--------------------------|
| Heat-trace Power Terminal Block | 5992000 | 1.27 |
| Heat-trace End Seal, SF-E | 5993000 | 0.05 |
| Heat-trace Tee Splice, SF-T | 5994000 | 1.18 |

Installation

Simply cut back one wire 1/4" (6mm) and push it into the end seal. For additional information, refer to the Uponor Ecoflex Pre-insulated Pipe Systems Design and Installation Manual.

Related applications

- Pre-Insulated Pipe Systems
- Permafrost Prevention Systems
- PEX-a Plumbing Systems

Codes

Standards

Listings

| | | |
|---|---|--------------------|
| - | - | IECEX SIR 11.0136U |
|---|---|--------------------|

Notes

Power cable:
3c x 2.5mm² (supplied by others)
Power cable entry: Gland provided as standard; insert appropriate supplied bush into the gland

Trademark information

ProPEX® is a registered trademark of Uponor Inc. ProPEX™ is a trademark of Uponor Ltd.

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.636.9517