

Stainless-steel manifold isolation valve bodies

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Brass
Temp/pressure ratings	68 °F (20 °C) at 145 psi (10 bar) 158 °F (70 °C) at 87 psi (6 bar) 194 °F (90 °C) at 44 psi (3 bar)
Prop 65 label required?	Yes

Product information and application use

Uponor's Stainless-steel Manifolds all come standard with isolation valves for easy loop isolation. These components are fixed to the return side of the manifold and are used to shut off the flow of water or water/glycol mix through the manifold port.



Part name	Part no.	Subcomponent Material	Weight per UOM [kg/UOM]
Stainless-steel Manifold Isolation Valve Body, replacement part	A2771030	Axle material (valve body): Brass	0.068
		CW614N-UNI EN 12164	
		Axle material (cap): Acrylonitrile butadiene styrene (ABS) plastic	
		Spring material (valve body): Stainless steel	
		O-ring material (valve body):	
O-ring for Stainless-steel Manifold Isolation Valve Body	A2771035	-	4.5359290943564E-4

Installation	Related applications
To operate the isolation valve on the Uponor Stainless-steel Manifold, twist the Stainless-steel Manifold On/Off Valve Plastic Cap clockwise to close and counterclockwise to open. For more information, refer to the Uponor Stainless-steel Manifold Installation Guide.	Radiant Heating and Cooling Systems
	Permafrost Protection Systems
	Turf Conditioning Systems

Notes

Maximum test pressure:
145 psi

Footnotes	Contact information
-	<div>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</div> <div>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</div>