

Two-wire thermal actuators for TruFLOW Classic and Jr. Valved Manifolds



Project information


Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Prop 65 label required? Yes

Product information and application use

The Uponor Two-wire Thermal Actuators are slow-opening thermal actuators that mount directly onto Uponor manifolds. They provide individual-loop flow control on multi-zoned manifolds.



Part name	Part no.	A [mm]	B [mm]	C [mm]	Current draw max. [A]	Operating voltage AC [VAC]	Weight per UOM [kg/UOM]
Two-wire Thermal Actuator for TruFLOW Classic and Jr. Valved Manifolds	A3030523	72.64	39.62	39.62	0.083	24	0.1134

Part name	Part no.	Codes	Standards	Listings
Two-wire thermal actuators for TruFLOW Classic and Jr. Valved Manifolds	A3030523	-	Class II wiring	-

Installation

Related applications

Mount directly onto the manifold. Refer to the manifold installation guide for detailed instructions.

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Notes

Time to Open/Close:
3 to 5 minutes

Footnotes

Contact information

-

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517